

## FIȘĂ TEHNICĂ PRODUS (Technical sheet)

|                                 |                                                                      |                                                                                     |
|---------------------------------|----------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Denumire produs<br>Product name | Banda PP 12 x 0,70 mm Manuală<br>PP strap 12 x 0,70 mm manual<br>use |  |
|---------------------------------|----------------------------------------------------------------------|-------------------------------------------------------------------------------------|

| CARACTERISTICI (CHARACTERISTICS)                |         |                                |                        |
|-------------------------------------------------|---------|--------------------------------|------------------------|
| Latime (mm)<br>Width (mm)                       | 12 mm   | Grosime (mm)<br>Thickness (mm) | 0,70 mm                |
| Dimensiune tub (mm)<br>Core Size (mm)           | 200x190 | Culoare<br>Colour              | Neagra<br>(Black)      |
| Lungime (m)<br>Roll Length (m)                  | 2500 m  | Suprafata<br>(Surface)         | Embosata<br>(Embossed) |
| Greutate rola (kg)<br>Average Gross Weight (kg) |         | 13,05 kg (± %3)                |                        |

| PROPRIETĂȚI MECANICE (MECHANICALS PROPERTIES) |     |         |                                             |     |          |
|-----------------------------------------------|-----|---------|---------------------------------------------|-----|----------|
| Minim (minimum)                               |     |         | Maxim (maximum)                             |     |          |
| Forța de rupere<br>Breaking<br>Strength       | kgf | 101     | Forța de rupere<br>Breaking<br>Strength     | kgf | 154      |
|                                               | N   | 990,406 |                                             | N   | 1510,124 |
| Elongatie (%)<br>Elongation (%)               |     | 12%     | Elongatie (%)<br>Elongation (%)             |     | 24%      |
| Temperatura de lucru<br>Working Temperature   |     | -25°    | Temperatura de lucru<br>Working Temperature |     | +75°     |

| TOLERANȚE (TOLERANCE RANGE)            |           |                                        |           |
|----------------------------------------|-----------|----------------------------------------|-----------|
| Minim (minimum)                        |           | Maxim (maximum)                        |           |
| Latime(mm)<br>Width (mm)               | 11,10 mm  | Latime(mm)<br>Width (mm)               | 12,00 mm  |
| Grosime (mm)<br>Thickness (mm)         | 0,62 mm   | Grosime (mm)<br>Thickness (mm)         | 0,7 mm    |
| Greutate(gr/m)<br>Weith (gr / m)       | 4,91 gr/m | Greutate(gr/m)<br>Weith (gr / m)       | 5,21 gr/m |
| Greutate rola(kg)<br>Gross Weight (kg) | 12,68 kg  | Greutate rola(kg)<br>Gross Weight (kg) | 13,43 kg  |

CAMPACK SRL  
Brasov, str. Zizinului 109 bis

Tel: +40268.330.988 / +40268.333.807  
E-mail: office@campack.ro  
Web: www.campack.ro